

HEAVY PROFESSIONAL WASHER EXTRACTORS

STATE-OF-THE-ART TECHNOLOGY

FEATURES

HPW-8 / HPW-10 TOUCH II

- High spin washer extractor. Soft mounted.
- G Force 450.
- Grey skinplate body. Stainless steel drum and tub.
- Detergent dispenser with 4 compartments.
- 8 signals for automatic liquid dosing, programmable in time and delay.
- 2 water inlets (hot and cold).
- These machines have electronic control of imbalance with frequency inverter, that detects the unbalanced load before spinning. Standard frequency: 50 60 Hz.
- New microprocessor TOUCH II with touch screen. 26 preset programs.
- Possibility of programming, exporting and importing programs without limit and software updates, through USB port, using USB drive.
- Traceability standard: All washing process (temperatures, water levels) is stored in the washer and can be extracted to a PC by means of a USB drive.
- Wet Cleaning standard in the microprocessor: fully adjustable water levels and washing speed for delicate linen.
- Optimal Loading standard to optimize water and chemicals consumption.
- Loading Aid feature with water and rotation control for easy loading of the linen.
- Model with drain valve and model with drain pump.
- Valve models especially designed for washing mops.
- Self-service version available with coin meter.
- · Leveling feet included.
- CE and WRAS approved.

OPTIONS

- Relay card with 6 extra dosing signals: up to 14 signals.
- WIFÍ module.
- AISI 304 stainless steel panels.
- Door silicone gasket.
- Reversible door opening.
- Delayed door opening in case of power outage.
- Self-service kits: Central pay with coin/token kit + box.
- Double drain (only valve models).
- Normally closed drain valve.
- Drain pump kit.
- Valve to pump model kit.
- Tropicalized model.
- Plinth for better ergonomics.
- Plinth for mops (filter included) only valve models.
- Plinth with tank for water recovery.







TECHNICAL DATA	UNIT.	HPW-8 V	HPW-8 P	HPW-10 V	HPW-10 P		
DRUM							
Load capacity 1:9 / 1:10	Kg	9/8	9/8	11/10	11/10		
Volume	I	80	80	100	100		
Diameter	mm	532	532	532	532		
Depth	mm	360	360	425	425		
GENERAL DETAILS							
Washing speed / Spining speed	r.p.m.	50/ 1.250	50/ 1.250	50/ 1.250	50/ 1.250		
G Force	-	450	450	450	450		
Self-service version	-	Yes	Yes	Yes	Yes		
Double drain	-	Yes	No	Yes	No		
Weighing system / tilting system	-	No	No	No	No		
DOOR							
Height center door / Height base door	mm	537/280	537/280	537/280	537/280		
Diameter	mm	373	373	373	373		
DYNAMIC FORCE							
Static Load	KN	1,4	1,4	1,5	1,5		
Maximum Dynamic load	KN	0,5	0,5	0,6	0,6		
Vertical maximum load	KN	0,64	0,64	0,75	0,75		
Max revolutions	r.p.m.	1.250	1.250	1.250	1.250		
Frequency of dynamic load	-	18,33	18,33	18,33	18,33		
POWER							
Motor	kW	0,75	0,75	0,75	0,75		
Electric heating	kW	6	6	6	6		
Hot water heating	kW	0	0	0	0		
Max. power electric model	kW	6,25	6,25	6,25	6,25		
Max. power HW model	kW	0,75	0,75	0,75	0,75		
Max. power steam	kW	No	No	No	No		
CONNECTIONS		'					
Water inlet	inch	3/4"	3/4"	3/4"	3/4"		
Drain	mm/inch	2"	1" (Pump)	2"	1" (Pump)		
DIMENSIONS / PACKING DIMENSIONS							
Width / width	mm	680/710	680/710	680/710	680/710		
Depth / depth	mm	698/832	698/832	742/832	742/832		
Height / height	mm	1.040/1.130	1.040/1.130	1.040/1.130	1.040/1.130		
Net weight / Gross weight	kg	140/150	140/150	150/160	150/160		









- 01. Soap dispenser 02. USB port
- 03. Drain
- 04. Main switch
- 05. Electric connection to liquid soap pumps
- 06. Electrical connection
- 07. Llquid soap inlet
- 08. Cold water inlet
- 09. Hot water inlet
- 10. Plinth height 389mm

	А	В	С	D	Е	F	G	Н	- 1	J	Κ	L	М	Ν	0	Р	Q
HPW-8 V	680	698	1040	278	373	86	964	962	922	944	954	110	366	453	528	603	199
HPW-8 P	680	698	1040	278	373	-	964	962	922	944	954	110	366	453	528	603	-
HPW-10 V	680	742	1040	278	373	86	964	962	922	944	954	110	366	453	528	603	199
HPW-10 P	680	742	1040	278	373	-	964	962	922	944	954	110	366	453	528	603	-



