

Front loading washer extractors




# Front washers

The new DOMUS high, medium and low spin front washers offer an advanced design and technology, combined with a huge variety of accessories and options.

High G Factor, the touchscreen TOUCH II microprocessor with many features, connectivity, versatility.

They are designed to satisfy the laundry needs of the most varied businesses, always taking into consideration efficiency and productivity as main goals.




# ECOVOLUTION by bomus

| $\bigcirc$ | HIGH SPIN WASHERS   G FACTOR 450 |                               |                    |                    |                    |                    |                    |                    |                    |                     |
|------------|----------------------------------|-------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|---------------------|
|            | CONTROL TYPE                     | HEATING                       | CAPACITY           |                    |                    |                    |                    |                    |                    |                     |
|            |                                  |                               | 10-11 kg           | 13-14 kg           | 18-20 kg           | 25-28 kg           | 35-38 kg           | 45-50 kg           | 60-65 kg           | 120-133 kg          |
|            | TOUCH II<br>Programmable Control | Electric, hot water and steam | DHS-11<br>TOUCH II | DHS-14<br>TOUCH II | DHS-18<br>TOUCH II | DHS-27<br>TOUCH II | DHS-36<br>TOUCH II | DHS-45<br>TOUCH II | DHS-60<br>TOUCH II | DHS-120<br>TOUCH II |
|            | TOUCH II COIN<br>Coin laundry    | Electric and hot water        | DHS-11<br>TOUCH II | DHS-14<br>TOUCH II | DHS-18<br>TOUCH II | DHS-27<br>TOUCH II | DHS-36<br>TOUCH II | -                  | -                  | -                   |

| ر ر | MEDIUM SPIN WASHERS   G FACTOR 300 |                               |                    |                    |                    |                    |  |  |  |
|-----|------------------------------------|-------------------------------|--------------------|--------------------|--------------------|--------------------|--|--|--|
|     | CONTROL TYPE                       | HEATING                       | CAPACITY           |                    |                    |                    |  |  |  |
|     |                                    |                               | 10-11 kg           | 13-14 kg           | 18-20 kg           | 25-28 kg           |  |  |  |
|     | TOUCH II<br>Programmable Control   | Electric, hot water and steam | DMS-11<br>TOUCH II | DMS-14<br>TOUCH II | DMS-18<br>TOUCH II | DMS-27<br>TOUCH II |  |  |  |
|     | TOUCH II COIN<br>Coin laundry      | Electric and hot water        | DMS-11<br>TOUCH II | DMS-14<br>TOUCH II | DMS-18<br>TOUCH II | DMS-27<br>TOUCH II |  |  |  |

| LOW SPIN WASHERS   G FACTOR 200  |                               |                    |                    |                    |                    |                    |                    |  |  |
|----------------------------------|-------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--|--|
| CONTROL TYPE                     | HEATING                       | CAPACITY           |                    |                    |                    |                    |                    |  |  |
|                                  |                               | 10-11 kg           | 13-14 kg           | 18-20 kg           | 25-28 kg           | 35-38 kg           | 60-66 kg           |  |  |
| TOUCH II<br>Programmable Control | Electric, hot water and steam | DLS-11<br>TOUCH II | DLS-14<br>TOUCH II | DLS-18<br>TOUCH II | DLS-27<br>TOUCH II | DLS-36<br>TOUCH II | DLS-60<br>TOUCH II |  |  |
| TOUCH II COIN<br>Coin laundry    | Electric and hot water        | DLS-11<br>TOUCH II | DLS-14<br>TOUCH II | DLS-18<br>TOUCH II | DLS-27<br>TOUCH II | DLS-36<br>TOUCH II | DLS-60<br>TOUCH II |  |  |

3



## **ECO**ENERGY



#### TOUCH II

- ▼TOUCH II, user friendly and totally programmable microprocessor with a 7" touch screen and 29 preset programs
- **USB Connection.** PC software free of charge for programming, traceability, data analysis...
- **⊘** Remote communication
- **⊘**Traceability standard
- **olimited Wet cleaning ready**
- Videos on display: ads, instructions (useful for coin laundry)
- **⊘** 37 languages
- **⊘** 8 dosing signals as standard + optional 6 extra dosing signals



#### G FACTOR

- High G-FACTOR for all range of washers comparing with competitors
  - **G-FACTOR 450** for High spin washers **G-FACTOR 300** for Medium spin washers **G-FACTOR 200** for Low spin washers
- High G-Factor reduces residual moisture and drying time



#### **VERSATILITY**

**⊘** Make to order: customisation

New possibility to customise the machines from factory with the available options

- **⊘** OPL < > Coin / Token
- Standard models easily transformable with coin/token kits
- Electric < > Hot water
  Standard electric models easily transformable to hot water models
- **⊘** Drain valve < > Pump

Standard models easily transformable Easy access and service

**⊘** Wet cleaning

All washers have all features to use wet cleaning programs



#### CONNECTIVITY

**⊘** Remote technical service

Machine monitoring, machine error warning, management for traceability and statistics.

Remote desk and data recovery for technicians and maintenance, software update, etc.

- Management for laundries: OPL and COIN Our DOMUS IoT solution allows you to manage your laundry business (i.e. create discount programs for customers, get statistics, traceability and laundry monitoring).
- Remote payment: App for payments, cashless payment by scanning a QR code, promotions and machine booking



Domus

#### **EFFICIENCY**

**⊘** Water savings

Possibility of configuring three levels of savings

- Optimal loading: manual indication of weight
- Intelligent Consumption: automatic adjustment of water and soap consumptions (standard)
- ✓ Prepared to be connected to water recovery tanks ECOTANK
- Low water consumption

Standard washing program consumes less than 7 liters of water per kg and cycle

- **∀** High G-FACTOR 450 for High spin machines
- Reduced residual moisture > reduced drying time
- **Water RE-CYCLE** (recirculation of bath water)



#### ERGONOMICS

- Biggest door diameters in the market Helpful, mainly for big capacity washers, for loading and unloading operations
- ✓ Easy opening/closing system for door lock
   ✓ Plinths for 11, 14, 18, 27 and 36 kg models
  - To align loading height (door base at 850 mm)



#### MAINTENANCE

- Hinged panel Easy and ergonomic access to control panel parts
- **⊘** Equivalent parts

Most key parts are the same for all models parts are same for all models (contactors, electronic devices, gear...)

- Easy access to parts for reparability
- Technical menu: traceability, error diagnosis, machine monitoring, software update...





## TOUCH II

The new TOUCH II is a substantial evolution from the previous microprocessor which includes many more features mainly based on achieving more efficiency, versatility and connectivity among others.

User friendly and totally programmable microprocessor with

### 7" touch screen and 29 preset programs

Configuration of washing and spinning speed Complete regulation of water levels Regulable washing temperature from 20°C to 90 °C Standard WET CLEANING system

#### Videos on display

Ads, instructions (useful for coin laundries)



8 dosing signals as standard + optional 6 extra dosing signals



#### 37 languages

Available and easy to configurate, thanks to DOMUS aim to be accessible to everyone.







#### **USB Connection**

PC software (Wash Control) free of charge for programming, traceability, data analysis...



# G-FACTOR

DOMUS washer extractors, whether high, medium or normal spin, are the ones with the highest G-Factor in the market, which ensures minimum residual moisture, and this translates into less energy costs during the drying cycle.



DOMUS washer extractors offer a wide variety of efficient features to make sure that the washing cycles use only the needed water and chemicals, not more.

# High G-Factor reduces residual moisture and drying time



#### **Water savings**

Possibility of configuring three levels of savings

## Low water consumption

A standard washing program consumes less than 7 litres of water per kg and cycle, and an ECO program up to 6 litres.

## Optimal loading

## Intelligent consumption

Automatic adjustment of water and soap (standard)

#### High G FACTOR 450 for high spin machines

Reduced residual moisture > reduced drying time

#### Water re-cycle

Optional kit to increase the care of the linen: recirculation of the bath water, which increases the water flow with chemicals, shortens the cycle and improves the effectiveness without mechanical action



## **ECOTANK**

# Ready to be connected to water recovery tanks

Domus washer extractors, with Touch II microprocessor and double drain, can be connected to the new Domus Ecotank which allows the water recovery, achieving important water and energy savings.



# VERSATILITY

To adapt to the needs of the different businesses and sectors with the smallest investment.

**DOMUS** washer extractors between 10 and 36 kg are specially designed to be used in coin laundry businesses. This is available both for soft mounted machines DHS and hard mounted machines DMS and DLS.

#### Make to order:

#### customization

New possibility to customize the machines from factory with the available options

## Electric <>> Hot water

Standard electric models easily transformable to hot water models

#### **Drain valve <>> Pump**

Standard models easily transformable Easy access and service

## Wet Cleaning<sup>®</sup>

Thanks to DOMUS constant development, our models are equipped with the features to use WET CLEANING programs:

- Fully programmable TOUCH II
- Total control of temperature and water levels
- Programmable washing speed: very low (13 R.P.M.)
- Rhythm on/off 3seg/40seg
- ✓ Total control of dosing signal



A new feature of Domus washers is its easy transformation from an OPL to a COIN machine.

Three available options:

OPL <> COIN

#### Coin / Token

There are several kits depending on the currency of each country, which can be used with a token or with a new mechanical coiner kit. Both to be ordered with a coin box kit.



#### **Central Pay**

The machines can be connected to the central pay with the central pay kit to control a single box with



#### Remote payment

Machines ready for remote communication: allows programming, management and technical feedback. Multi payable systems: price updating, etc.



### **Open system**

Domus equipment is prepared to work with any external payment system (by means of multi-point data).



12





Responsibe App, native for tablets and smartphones. Offline version available









## **Benefits for** the dealer

#### Remote technical management

Machine monitoring. Machine error warning. Management for traceability and statistics. Remote desk and data recovery for technicians and maintenance. Software update. Renting of machines. Invoicing by cycles.

APP for the owner / dealer



**Industrial/OPL laundry** 



## **Benefits for** the owner

#### Laundry management

Production and program/cycles. Working times. Management for traceability and statistics. Download of data in excel. Remote desk and data recovery for technicians and maintenance. Software update. Renting of machines.

#### **Coin laundry management**

To monitor the business:

- control of opening times
- control of income
- creation of machine groups (shops, models, etc.)

Management for traceability and statistics.

Remote desk and data recovery for technicians and maintenance

Software update.

Renting of machines.

## **Benefits for** the owner

Domus

- create programs/discounts

Download of data in excel.



## **Benefits for** the user

#### **Customizable app**

according to type of customer: neighbourhood association, boarding schools, etc.

Booking of machines: availability of free machines and booking.

Cashless payment by QR code, promotions. Push notifications/contact by means of an e-mail. Year-to-date invoicing.

Client fidelity by means of promotions, cards, discounts, etc.



#### Location

of machines registered all over the globe

IOT available in all **TOUCH II washers and** dryers. Connection by WIFI or Ethernet



850 mm

## ERGONOMICS

As health and safety at work had become an important issue, our equipment is designed to be the most comfortable for the user.



## MAINTENANCE

One of DOMUS concerns is to make life easier for our clients. That includes offering quality equipment and parts of reputed brands, which demand little maintenance.

# Biggest door diameters in the market

Helpful, mainly for big capacity washers, for loading and unloading the garments

### Plinths for 11, 14, 18, 27 and 36 kg models

To align loading height (door base at 850 mm)

#### Easy opening/ closing system for door lock

## Reversible door

# Easy access for reparability

Washers are designed to offer an easy maintenance and reparability

#### **Equivalent parts**

Most key parts are the same for all models (contactors, eletronic devices, gear,...)

#### Hinged panel

Easy and ergonomic acces to the panel

#### **Technical menu**

Machine monitoring, machine error warning, management for traceability and statistics.
Remote desk and data recovery for technicians and maintenance, software update, etc.



#### Domus

#### Washer extractors technical data

| (i) HIGH SPIN                         |        |          |           |           |           |           |             |             |             |
|---------------------------------------|--------|----------|-----------|-----------|-----------|-----------|-------------|-------------|-------------|
|                                       | UNIT.  | DHS-11   | DHS-14    | DHS-18    | DHS-27    | DHS-36    | DHS-45      | DHS-60      | DHS-120     |
| DRUM                                  |        |          |           |           |           |           |             |             |             |
| Load capacity (kg) 1:9 / 1:10         | Kg     | 11/10    | 14/13     | 20/18     | 28/25     | 39/35     | 50/45       | 67/60       | 133/120     |
| Volume                                |        | 100      | 130       | 180       | 250       | 350       | 450         | 600         | 1200        |
| Diameter                              | mm     | 532      | 620       | 700       | 770       | 860       | 918         | 1048        | 1360        |
| Depth                                 | mm     | 425      | 430       | 470       | 530       | 602       | 720         | 684         | 840         |
| GENERAL DETAILS                       |        |          |           |           |           |           |             |             |             |
| Washing speed / Spining speed         | r.p.m. | 50/1.231 | 50/1.138  | 47/1.071  | 45/1.024  | 42,5/966  | 42,5/934    | 38/875      | 34/678      |
| G Factor                              | -      | 450      | 450       | 450       | 450       | 450       | 450         | 450         | 350         |
| Noise level                           | dB     | < 70     | < 70      | < 70      | < 70      | < 70      | < 70        | < 70        | < 70        |
| Coin laundry version                  | -      | YES      | YES       | YES       | YES       | YES       | N0          | NO          | N0          |
| Double drainage                       | -      | EXTOPT   | OPT.      | OPT.      | OPT.      | OPT.      | OPT.        | OPT.        | OPT.        |
| Weighing System                       | -      | OPT.     | OPT.      | OPT.      | OPT.      | OPT.      | OPT.        | OPT.        | OPT.        |
| Tilting System                        | -      | NO       | NO        | N0        | NO        | N0        | OPT.        | OPT.        | OPT.        |
| SLUICE option                         | -      | NO       | NO        | NO        | NO        | N0        | NO          | NO          | N0          |
| DOOR                                  |        |          |           |           |           |           |             |             |             |
| Height center door / Height base door | mm     | 630/370  | 700 / 440 | 765 / 450 | 865 / 560 | 885 / 540 | 1.190 / 830 | 1.190 / 830 | 1.330 / 900 |
| Diameter                              | mm     | 373      | 373       | 460       | 460       | 560       | 560         | 560         | 700         |
| POWER                                 |        |          |           |           |           |           |             |             |             |
| Motor                                 | kW     | 0,75     | 1,1       | 2,2       | 4         | 4         | 7,5         | 11          | 15          |
| Electric heating power                | kW     | 6        | 9         | 12        | 18        | 21        | 28,8        | 36          | -           |
| Total electric power (electric model) | kW     | 6,25     | 9,4       | 12,75     | 19,2      | 22        | 31,3        | 40          | -           |
| Total electric power (steam model)    | kW     | 0,75     | 1,1       | 2,2       | 4         | 4         | 7,5         | 11          | 15          |
| CONNECTIONS                           |        |          |           |           |           |           |             |             |             |
| Steam intake (steam mod.)             | inch   | 1/2"     | 1/2"      | 1/2"      | 3/4"      | 3/4"      | 3/4"        | 3/4"        | 1-1/4"      |
| Water intake                          | inch   | 3/4"     | 3/4"      | 3/4"      | 3/4"      | 3/4"      | 1"          | 1"          | 1-1/2"      |
| Drain                                 | inch   | 3"       | 3"        | 3"        | 3"        | 3"        | 3"          | 3"          | 4"          |
| DIMENSIONS                            |        |          |           |           |           |           |             |             |             |
| Width                                 | mm     | 692      | 788       | 884       | 979       | 1.095     | 1.478       | 1.478       | 1.836       |
| Depth                                 | mm     | 788      | 869       | 913       | 1.041     | 1.184     | 1.444       | 1.444       | 1.863       |
| Height                                | mm     | 1.185    | 1.307     | 1.415     | 1.553     | 1.598     | 1.945       | 1.945       | 2.245       |
| Net weight                            | kg     | 230      | 250       | 360       | 490       | 750       | 1.350       | 1.400       | 3.950       |
| PACKING DIMENSIONS                    |        |          |           |           |           |           |             |             |             |
| Width                                 | mm     | 730      | 830       | 930       | 1.040     | 1.165     | 1.540       | 1.540       | 1.900       |
| Depth                                 | mm     | 1.000    | 1.010     | 1.030     | 1.160     | 1.230     | 1.580       | 1.580       | 1.940       |
| Height                                | mm     | 1.417    | 1.560     | 1.700     | 1.850     | 1.920     | 1.970       | 1.970       | 2.290       |
| Gross weight                          | kg     | 239      | 283       | 393       | 545       | 820       | 1.420       | 1.520       | 4.100       |
| Volume                                | $m^3$  | 1,03     | 1,31      | 1,63      | 2,23      | 2,75      | 4,79        | 4,79        | 8,44        |

|  | UNIT.                | DMC 44                            | DMC 44                            | DMC 46                              | DMC 07                                |
|--|----------------------|-----------------------------------|-----------------------------------|-------------------------------------|---------------------------------------|
|  | UNII.                | DMS-11                            | DMS-14                            | DMS-18                              | DMS-27                                |
| UM   |                      |                                   |                                   |                                     |                                       |
| ad capacity (kg) 1:9 / 1:10  | Kg                   | 11/10                             | 14/13                             | 20/18                               | 28/25                                 |
| lume   | I                    | 100                               | 130                               | 180                                 | 250                                   |
| ameter   | mm                   | 620                               | 620                               | 700                                 | 770                                   |
| epth   | mm                   | 330                               | 430                               | 470                                 | 530                                   |
| NERAL DETAILS  |                      |                                   |                                   |                                     |                                       |
| ashing speed / Spining speed   | r.p.m.               | 50/929                            | 50/929                            | 45/874                              | 40/836                                |
| Factor   | -                    | 300                               | 300                               | 300                                 | 300                                   |
| pise level   | dB                   | < 70                              | < 70                              | < 70                                | < 70                                  |
| in laundry version   | -                    | YES                               | YES                               | YES                                 | YES                                   |
| ouble drain  | -                    | EXTOPT                            | EXTOPT                            | OPT.                                | OPT.                                  |
| eighing System   | -                    | NO                                | N0                                | NO                                  | NO                                    |
| ting System  |                      | NO                                | N0                                | NO                                  | NO                                    |
| UICE option  | -                    | N0                                | N0                                | N0                                  | NO                                    |
| OOR  |                      |                                   |                                   |                                     |                                       |
| eight center door / Height base door                                 | mm                   | 570/310                           | 570/310                           | 655 / 348                           | 700 / 40                              |
| ameter   | mm                   | 373                               | 373                               | 460                                 | 460                                   |
| OWER   |                      |                                   |                                   |                                     |                                       |
| otor   | kW                   | 1,1                               | 1,1                               | 2,2                                 | 3                                     |
| eating (Electric model)  | kW                   | 6                                 | 9                                 | 12                                  | 18                                    |
| ax. power (Electric model)   | kW                   | 6,25                              | 9,5                               | 12,75                               | 19                                    |
| ax. power (Steam and HW model)                                       | kW                   | 1,1                               | 1,1                               | 2,2                                 | 3                                     |
| ONNECTIONS   |                      |                                   |                                   |                                     |                                       |
| eam intake (steam mod.)  | inch                 | 1/2"                              | 1/2"                              | 1/2"                                | 3/4"                                  |
|  | inch                 | 3/4"                              | 3/4"                              | 3/4"                                | 3/4"                                  |
| ater intake  | inch                 | 3"                                | 3"                                | 3"                                  | 3"                                    |
| ain  |                      |                                   |                                   |                                     |                                       |
| ain<br>MENSIONS  |                      | <b>3</b> .6-                      |                                   | ====                                |                                       |
| ain<br>MENSIONS<br>idth  | mm                   | 719                               | 719                               | 788                                 | 884                                   |
| ain<br>MENSIONS<br>idth<br>epth                                      | mm<br>mm             | 684                               | 830                               | 840                                 | 1.011                                 |
| ain<br>MENSIONS<br>idth<br>epth                                      | mm<br>mm             | 684<br>1.158                      | 830<br>1.158                      | 840<br>1.307                        | 1.011<br>1.340                        |
| MENSIONS idth epth eight et weight                                   | mm<br>mm             | 684                               | 830                               | 840                                 | 1.011                                 |
| ain MENSIONS idth epth eight et weight ACKING DIMENSIONS             | mm<br>mm<br>mm<br>kg | 684<br>1.158<br>217               | 830<br>1.158<br>239               | 840<br>1.307<br>281                 | 1.011<br>1.340<br>340                 |
| ain  MENSIONS  idth  epth  eight  et weight  ACKING DIMENSIONS  idth | mm<br>mm<br>mm<br>kg | 684<br>1.158<br>217<br>800        | 830<br>1.158<br>239<br>800        | 840<br>1.307<br>281<br>840          | 1.011<br>1.340<br>340<br>930          |
| MENSIONS idth epth eight et weight CKING DIMENSIONS idth             | mm<br>mm<br>mm<br>kg | 684<br>1.158<br>217<br>800<br>990 | 830<br>1.158<br>239<br>800<br>990 | 840<br>1.307<br>281<br>840<br>1.010 | 1.011<br>1.340<br>340<br>930<br>1.150 |
| ain  MENSIONS  idth  epth  eight  et weight  ACKING DIMENSIONS  idth | mm<br>mm<br>mm<br>kg | 684<br>1.158<br>217<br>800        | 830<br>1.158<br>239<br>800        | 840<br>1.307<br>281<br>840          | 1.011<br>1.340<br>340<br>930          |
| ain<br>MENSIONS  |                      |                                   |                                   |                                     |                                       |

|  | -  | _  | _  | -  | _  |
|--|--|--|--|--|--|
| ( ) r                                      | OW SPIN                                    |  |  |  |  |
| DLS-11                                     | DLS-14                                     | DLS-18                                       | DLS-27                                       | DLS-36   | DLS-60   |
|  |  |  |  |  |  |
| 44.440                                     |  | 00/10  | 00/05  | 00/05  | 07.400   |
| 11/10                                      | 14/13                                      | 20/18  | 28/25  | 39/35  | 67/60  |
| 100  | 130  | 180  | 250  | 350  | 600  |
| 620  | 620  | 700  | 770  | 860  | 1048   |
| 330  | 430  | 470  | 530  | 602  | 684  |
| 53/759                                     | 53/759                                     | 50/714                                       | 48/682                                       | 45/644   | 42,5/505   |
| 200  | 200  | 200  | 200  | 200  | 150  |
| < 70                                       | < 70                                       | < 70   | < 70   | < 70   | < 70   |
| YES  | YES  | YES  | YES  | YES  | YES  |
| NO   | OPT.                                       | OPT.   | OPT.   | OPT.   | OPT.   |
| NO   | NO   | NO   | NO   | NO   | NO   |
| NO   | NO   | NO   | NO   | NO   | NO   |
| YES  | YES  | YES  | YES  | YES  | NO   |
| F70 /040                                   | F70 /040                                   | 055 / 040                                    | 700 / 400                                    | 705 / 440  | 000 / 540  |
| 570/310                                    | 570/310                                    | 655 / 348                                    | 700 / 400                                    | 735 / 440  | 900 / 540  |
| 373  | 373  | 460  | 460  | 560  | 560  |
| 1,1  | 1,1  | 2,2  | 3  | 4  | 5,5  |
| 6  | 9  | 12   | 18   | 21   | 28,8   |
| 6,25                                       | 9,5  | 12,75  | 19   | 22   | 31,3   |
| 1,1  | 1,1  | 2,2  | 3  | 4  | 5,5  |
|  |  |  |  |  |  |
| 1/2"                                       | 1/2"                                       | 1/2"   | 3/4"   | 3/4"   | 3/4"   |
| 3/4"                                       | 3/4"                                       | 3/4"   | 3/4"   | 3/4"   | 3/4"   |
| 3"   | 3"   | 3"   | 3"   | 3"   | 3"   |
| 719  |  |  |  |  | 4005   |
|  | 719  | 788  | 884  | 979  | 1225   |
|  | 719<br>684                                 | 788<br>840                                   | 965  | 979  | 1225   |
| 684  | 684  | 840  | 965  | 1.066  | 1.279  |
| 684<br>1.158                               | 684<br>1.158                               | 840<br>1.307                                 | 965<br>1.340                                 |  |  |
| 684  | 684  | 840  | 965  | 1.066<br>1.411                                   | 1.279<br>1.640                                   |
| 684<br>1.158                               | 684<br>1.158                               | 840<br>1.307<br>281                          | 965<br>1.340                                 | 1.066<br>1.411                                   | 1.279<br>1.640                                   |
| 684<br>1.158<br>217                        | 684<br>1.158<br>239                        | 840<br>1.307                                 | 965<br>1.340<br>340                          | 1.066<br>1.411<br>473                            | 1.279<br>1.640<br>930                            |
| 684<br>1.158<br>217<br>800                 | 684<br>1.158<br>239<br>800                 | 840<br>1.307<br>281<br>840                   | 965<br>1.340<br>340<br>930                   | 1.066<br>1.411<br>473<br>1.050                   | 1.279<br>1.640<br>930<br>1.360                   |
| 684<br>1.158<br>217<br>800<br>990          | 684<br>1.158<br>239<br>800<br>990          | 840<br>1.307<br>281<br>840<br>1.010          | 965<br>1.340<br>340<br>930<br>1.150          | 1.066<br>1.411<br>473<br>1.050<br>1.250          | 1.279<br>1.640<br>930<br>1.360<br>1.480          |
| 684<br>1.158<br>217<br>800<br>990<br>1.350 | 684<br>1.158<br>239<br>800<br>990<br>1.350 | 840<br>1.307<br>281<br>840<br>1.010<br>1.500 | 965<br>1.340<br>340<br>930<br>1.150<br>1.523 | 1.066<br>1.411<br>473<br>1.050<br>1.250<br>1.600 | 1.279<br>1.640<br>930<br>1.360<br>1.480<br>1.880 |

18

<sup>\*</sup>DOMUS reserves the right to modify the technical data without notice.



C. Energia, 12 - Pol. Ind. La Quintana 08504 Sant Julià de Vilatorta BARCELONA (SPAIN)

#### SALES DEPARTMENT

T. +34 93 812 27 96 M. +34 649 482 730 **F**. +34 93 888 76 63 domus@domuslaundry.com export@domuslaundry.com

#### AFTER SALES DEPARTMENT

T. +34 93 888 76 73 F. +34 93 888 76 63 sat@domuslaundry.com

#### PARTS DEPARTMENT

T. +34 93 888 76 83 F. +34 93 888 76 63 parts@domuslaundry.com







